



# Cross Check™

## Torque Seal® Tamper-Proof Indicator Paste

### HANDLING

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Do not handle, store or open near an open flame, sources of heat or sources of ignition.
- Protect material from direct sunlight. Explosion-proof

### DRY TIME

- Dry to touch/handle in 30-40 minutes.
- 80% curing occurs between 48-72 hours. Completion of curing takes place between 7-10 days.
- Exposing to elevated temperature OR blowing hot air can speed up the drying/curing process.

### STORAGE

- Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well

### DISPOSAL INFORMATION

- Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

### FEATURES

- Tamper Proof Torque Mark
- Safe for most surfaces
- Highly visible- all colors are fluorescent
- Excellent adhesion
- Visually detects loose nuts & bolts
- Provides warranty protection
- Meets BOEING Specification, BMS8-45 Type II



### PHYSICAL PROPERTIES

Physical State	Liquid
Odor	mild
Flash Point	105.1 °F (40.6 °C)
Boiling Point	276.98 - 485.06 °F (136.1 - 251.7 °C)
VOC Content	42.28%, 430 g/L
Vapor Density	> 1 (air = 1)
Prop 65 Warning	YES

### AVAILABLE IN

Color	Net Contents	Container Type	Units/Case	Part #
orange	1 oz	tube	24	83314
green	1 oz	tube	24	83315
red	1 oz	tube	24	83316
yellow	1 oz	tube	24	83317
blue	1 oz	tube	24	83318
white	1 oz	tube	24	83319
pink	1 oz	tube	24	83320
gray	1 oz	tube	24	83321



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved