



# CITGO CITGEAR® MGW-UGL

## OVERVIEW




- An asphaltic, open gear lubricant designed to protect heavily loaded open gears with a heavy, dense film that includes extreme pressure additives to ensure smooth operation, even on gears that operate under harsh conditions.
- Contains a solvent for ease in handling and application.

## FEATURES & BENEFITS




- Resistance to sludge and deposit formation.
- High film strength.
- Excellent wear protection.
- Extends gear life.
- Protects against rust and corrosion.
- Water wash-off protection.
- Suitable for use in airless spray systems.
- Non-chlorinated.

## APPLICATIONS



- Recommended for grinding mill gear and pinion, ball grinding mill gear and pinion, girth gears, SAG mill gears, and cement kiln open gears.
- Approved by Shanghai Heavy Industries.

**PROPERTIES****Typical Properties for CITGO CITGEAR MGW-OGL:**

<b>Material Code</b>	<b>631056001</b>
Texture	Smooth
Color	Black
Flash Point, ASTM D92, °F (°C) (without diluent)	475 (246)
Flash Point, ASTM D92, °F (°C) (with diluent)	240 (116)
Viscosity ASTM D445 100°C, cSt (without diluent)	1000-2300
Viscosity ASTM D445 40°C, cSt (with diluent)	900-1600
Four Ball Weld EP, ASTM D2783, kg	500
Four Ball Wear, ASTM D4172, mm	0.33
Four Ball LWI, ASTM D2783, kgf	83
Copper Corrosion, ASTM D130	3B
Rust Prevention, ASTM D665	Pass
FZG, ASTM D5182, Load Stages Passed	>12
USS Mobility, @ 0° C, gls	1.65

CITGO and CITGEAR are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.