

85W-140

TECHNICAL DATA SHEET MOLY GEAR LUBRICANT

广州孚润 400-992-6811

SWACO Moly Gear Lubricant is specially designed for enclosed gear boxes. Inhibited with a synthetic thickener, it has excellent thermal stability and resistance to oxidation. It offers superb corrosion protection.

FEATURES:

Withstands pressures up to 100,000 PSI.
Fluid film does not "drain off" parts
Reduces frictional wear
Multi-Viscosity
Plates itself to metal surfaces

BENEFITS:

Peak power demand is lowered
Reduces inventory of many single weight oils
Reduces parts replacement--heals wear scars
Cooler gear box temperatures

Typical Specifications

Appearance	Opaque
Color	Black
Odor	Sulfur
Viscosity @ 40 C, cST	372
Viscosity @ 100 C, cST	27.74
Viscosity Index (min)	101
Pour Point	10 F
Flash Point, COC	495 F
Gravity degrees API	.8944

**THIS HEAVY DUTY OIL IS SUITABLE FOR USE IN THE GEAR BOXES OF
AUTOMATIC PIN SETTERS.
IT IS LEAK RESISTANT AND CAN PROVIDE LIMITED SEALING OF
DAMAGED SEALS/GASKETS.**

Sold by Dri-Slide North America—1452 Delashmut Avenue—Columbus, Ohio 43212
Website: www.russack.com Tel. #1-800-231-6901 or (614) 291-6929
Email: russack@netwalk.com