

High temperature and
Long life grease

广州孚润 400-992-6811

MULTEMP ET-K

MULTEMP ET-K is designed especially for use in rolling bearings of automobile electrical equipment such as alternators and electromagnetic clutches. MULTEMP ET-K has long performance life under high temperature and high speed conditions, together with excellent rust preventive properties.

Typical analyses

Usage temperature range $-40^{\circ}\text{C} \leftrightarrow 200^{\circ}\text{C}$

Test item		Test method	MULTEMP ET-K
Thickener		————	aromatic diurea
Base oil		————	ether-based synthetic oil + polyolester
Base oil kinematic viscosity (40°C) mm ² /s		ASTM D 445	95.1
Appearance		————	light brown, buttery
Worked penetration		ASTM D 217	300
Dropping point °C		ASTM D 566	230
Oil separation mass%	100°C,24h	FTMS 791C-321 Mod.	1.0
	150°C,24h		1.6
Low-temperature torque N·cm	(-30°C) Starting torque	ASTM D 1478-63	33
	Running torque		9.6
Corrosion preventive properties (52°C,48h)		ASTM D 1743-73	# 1

01/2

KYODO YUSHI Co., LTD.

2-16-7, Ginza, Chuo-ku, Tokyo 104-0061, Japan

Phone: (03) 3543-5814 Facsimile: (03) 3545-6259