

DESCO 960 Body Fill



PERFORMANCE UNDER PRESSURE SINCE 1986

广州孚润 400-992-6811

Description:

Formulated for gate valves that contain body cavities. Desco 960 is an economical body fill that will displace water and other contaminants. Desco 960 has high metal adhesion to lubricate and seal gates as they enter the body cavity.

Typical Characteristics:

Appearance	Gray, smooth
NLGI	2
Penetration (ASTM D217)	255-265
Worked Penetration, 60x (ASTM D217)	255-265
Base Oil	Mineral oil
Base Oil Viscosity	145 cSt at 40°C
Base Oil Pour Point	-10°F (-23 °C)
Thickener	Inorganic
Additives	Antioxidant/corrosion inhibitor package
Specific Gravity	.9
Density (lb/gal)	7.8
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>400°F (204°C)
Temperature Range	-10°F to 350°F (-23°C to 177°C)

Packaging Information:

Item No.	Unit Size	Quantity	Ship Wt.
LL960200	14 oz. cartridges	10 ctn.	12 lbs.
LL960010	10 lb can	1 each	11 lbs.
LL960020	20 lb can	1 each	23 lbs.
LL960040	40 lb pail	1 each	45 lbs.
LL960120	120 lb keg c/w liner	1 each	130 lbs.
LL960400	400 lb drum c/w liner	1 each	438 lbs.



Supplying the
Highest Quality Products
to the Valve Industry

#310, 8810 - 15 St
Edmonton, AB | T6P 0B9 | 780.416.4823
GRMFLOW.COM SALES@GRMFLOW.COM



DES_960_09/18