

# DESCO BLACK STEM-PAK Injectable Packing



PERFORMANCE UNDER PRESSURE SINCE 1986

广州孚润 400-992-6811

## Description:

Desco Black Stem-Pak is a non-curing pumpable packing that contains a blend of non-asbestos fibers and fillers in synthetic oils. Desco Black Stem-Pak is specifically designed for high temperature hydrocarbon service. Pumpable with a high pressure (10,000 psi) lubrication hand gun.

## Service Recommendations:

Aliphatic hydrocarbons, asphalt, hot oil and steam. Excellent in geothermal applications.

## Typical Characteristics:

Appearance	Black
NLGI	>6
Penetration (ASTM D217)	50-60
Base Oil	Synthetic and natural esters
Base Oil Viscosity	500 cSt at 40°C
Base Oil Pour Point	-4°F (-16°C)
Solids Content	Synthetic fibers, fillers
Specific Gravity	1.4
Density (lb/gal)	11.8
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>550°F (288°C)
Temperature Range	-90°F to 750°F (-40°C to 399°C)

## Packaging Information:

Item No.	Unit Size	Quantity	Ship Wt.
LP823110	"B" stick 3/8" x 1 1/2"	72 /box	.5 lbs.
LP823115	"C" stick 7/16" x 2 1/8"	32 /box	.5 lbs.
LP823130	"D" stick 1/2" x 2 1/4"	28 /box	.5 lbs.
LP823140	"G" stick 5/8" x 3 1/2"	14 /box	.5 lbs.
LP823150	"J" stick 1 3/8" x 8 1/2"	16 /box	10 lbs.
LP823160	"K" stick 1 1/2" x 10 1/2"	12 /box	11 lbs.
	1 1/2" x 7" stick	12 /box	11 lbs.
	3/8" x 3/4" stick	120 /box	20 lbs.
	3/8" x 1" stick	100 /box	20 lbs.
LP823170	3/4" x 4" stick	10 /box	10 lbs.
	5/8" x 3" stick	140 /box	25 lbs.
	2" x 1/8" ribbon, 1 gal.		11 lbs.
LP823016	16 oz.	12 /cnt.	30 lbs.
LP823040	40 lb pail	1 each	43 lbs.



Supplying the  
Highest Quality Products  
to the Valve Industry

#310, 8810 - 15 St  
Edmonton, AB | T6P 0B9 | 780.416.4823  
GRMFLOW.COM SALES@GRMFLOW.COM

