

DESCO 620

Gate Valve Lubricant for WKM Type Valves



PERFORMANCE UNDER PRESSURE SINCE 1986

广州孚润 400-992-6811

Description:

“Peanut butter” synthetic lubricant / sealant for use in gate valves with liquid and gas hydrocarbon service. 100% synthetic.

Service Recommendations:

Aliphatic hydrocarbons, alkalis, dilute acids, salt water and water.

Typical Characteristics:

Appearance	Brown, "peanut butter"
NLGI	0/00
Penetration (ASTM D217)	355-385 / 410-415
Worked Penetration, 60x (ASTM D217)	355-385 / 410-415
Base Oil	Natural and synthetic
Base Oil Viscosity	500 cSt at 40°C
Base Oil Pour Point	-4°F (-20 °C)
Thickener	Inorganic
Additives	Antioxidant package
Solids Content	Natural minerals
Specific Gravity	1.5
Density (lb/gal)	12.6
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>450°F (232°C)
Temperature Range	0°F to 300°F (-18°C to 149°C)

Packaging Information:

Item No.	Unit Size	Quantity	Ship Wt.
LL620200	14 oz. cartridges	10 ctn.	12 lbs.
LL620010	10 lb can	1 each	11 lbs.
LL620020	20 lb can	1 each	23 lbs.
LL620040	40 lb pail	1 each	45 lbs.
LL620120	120 lb keg c/w liner	1 each	130 lbs.
LL620400	400 lb drum c/w liner	1 each	438 lbs.



Supplying the
Highest Quality Products
to the Valve Industry

#310, 8810 - 15 St
Edmonton, AB | T6P 0B9 | 780.416.4823
GRMFLOW.COM SALES@GRMFLOW.COM



DES_620_09/18