

Rust Inhibited

A PTFE thickened, medium viscosity, synthetic hydrocarbon grease intended for automotive and industrial controls which require a light tack and minimal change in damping characteristics with temperature.

Lubricant Properties		Typical value	Test Method
Recommended Service Range (°C)		-40 to 125	
Thickener		PTFE	
Base oil	Type	Polyalphaolefin	
	Kinematic viscosity	> 1000000 cSt	ASTM D-445
		40°C	5548 cSt
		100°C	525 cSt
	Viscosity Index	280	ASTM D-2270
	Flash point	> 200	ASTM D-92
	Pouring point	-30	ASTM D-97
Typical Properties of the Grease		Typical value	Test Method
Color, Appearance		White	
Penetration (1/10 mm)	NLGI Grade	2	ASTM D-217
	Worked	60X	ASTM D-217
	Unworked	293	ASTM D-217
Density	25°C	1.16 g/cm ³	NYE CTM
Oil Separation	24 hour(s)	100°C	0
			FTM 791, Method 321.2
Evaporation	24 hour(s)	100°C	0.2

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1510)

Distributed by Newgate Simms Limited

Broughton Mills Road, Bretton, Chester, CH4 0BY, United Kingdom
+44(0)1244 660771 www.newgatesimms.com info@newgatesimms.com