

A silica thickened, medium viscosity, synthetic hydrocarbon grease intended for sliding, bearing and gear train applications. Regulations require that any addition to food not exceed 10 parts per million.

NSF H-1 Registered #128785

Lubricant Properties		Typical Value	Test Method
Recommended Service Range (°C)		-35 to 120	
Thickener		Silica	
Base Oil	Type	Polyalphaolefin	
	Kinematic Viscosity	40°C 100°C	194 cSt 22.8 cSt
	Viscosity Index	152	ASTM D-2270
	Flash Point	°C	235 ASTM D-92
	Pour Point	°C	-40 ASTM D-97
Typical Properties of the Grease		Typical Value	Test Method
Color, Appearance		Clear, Smooth	
Penetration (1/10 mm)	NLGI Grade	2	ASTM D-217
	Worked	60X	291 ASTM D-217
	Unworked	272	ASTM D-217
Density	25°C	0.88 g/cm ³	NYE CTM
Oil Separation	24 hour(s)	100°C	2 ASTM D-6184
Evaporation	24 hour(s)	100°C	0.2 % ASTM D-972
	100°C	0	

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (2001)