

## EP Fortified

A PTFE thickened, medium viscosity, completely fluorinated grease intended for use in wide temperature applications.

Lubricant Properties		Typical Value	Test Method
<b>Recommended Service Range (°C)</b>		-65 to 250	
<b>Thickener</b>		PTFE	
<b>Base Oil</b>	Type	Perfluoropolyether	
	Kinematic Viscosity	100°C	ASTM D-445
		40°C	ASTM D-445
	Viscosity Index	340	ASTM D-2270
	Pour Point	°C	ASTM D-97
	<b>Typical Properties of the Grease</b>	<b>Typical Value</b>	<b>Test Method</b>
<b>Color, Appearance</b>		Gray-black	
<b>Penetration (1/10 mm)</b>	Unworked	269	ASTM D-217
	Worked	60 X	ASTM D-217
	NLGI Grade	2	ASTM D-217
<b>Density</b>	25°C	1.89 g/cm <sup>3</sup>	ASTM D-70
<b>Oil Separation</b>	24 hour(s)	100°C	ASTM D-6184
<b>Evaporation</b>	24 hour(s)	100°C	NYE CTM

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product MSDS for detailed safety information because this product.

(1402)