

EP Fortified, Rust Inhibited

A lithium soap thickened, blended base oil gear grease suited for long life metal gears in automotive starters, power tools, and heavily loaded mechanical applications.

Lubricant Properties		Typical value	Test Method
Recommended Service Range (°C)		-50 to 130	
Thickener		Lithium Soap	
Base oil	Type	PAO/Ester	
	Kinematic viscosity	100°C	6.228 cSt
		40°C	33.593 cSt
		-40°C	14410 cSt
	Viscosity Index		136.7
	Flash point	°C	252
	Pouring point	°C	-52
Typical Properties of the Grease		Typical value	Test Method
Color, Appearance		Black, Smooth	
Penetration	Worked	60X	275
(1/10 mm)	Worked	10K	292
	Unworked		261
	NLGI Grade		2
Density		25°C	0.91 g/cm ³
Oil Separation	24 hour(s)	100°C	4.5 %
Evaporation	24 hour(s)	100°C	0.22 %
		150°C	2.76 %

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1511)

Distributed by Newgate Simms Limited

Broughton Mills Road, Bretton, Chester, CH4 0BY, United Kingdom
+44(0)1244 660771 www.newgatesimms.com info@newgatesimms.com