

SKF High load, high temperature, high viscosity bearing grease


LGHB 2

SKF LGHB 2 is a high viscosity, mineral oil based grease, using the latest complex calcium-sulphonate soap technology. Formulated to withstand high temperatures and extreme loads, it is suitable for a wide range of applications, especially in the cement, mining and metals segments. This grease contains no additives and the extreme pressure properties arise from the soap structure.

- Excellent load capacity, anti-oxidation and corrosion protection even with large water ingress
- Withstands peak temperatures of 200 °C (390 °F)

Typical applications

- Steel on steel plain bearings
- Pulp and paper making machines
- Asphalt vibrating screens
- Continuous casting machines
- Sealed spherical roller bearings operating up to 150 °C (300 °F)
- Work roll bearings in steel industry
- Mast rollers of fork lift trucks



Available pack sizes

Packsize	Designation	Packsize	Designation
420 ml cartridge	LGHB 2/0.4	Electro-mechanical lubricators	
5 kg can	LGHB 2/5	TLSD series 125 ml	TLSD 125/HB2
18 kg pail	LGHB 2/18	TLSD series 125 ml refill	LGHB 2/SD125
50 kg drum	LGHB 2/50	TLSD series 250 ml	TLSD 250/HB2
180 kg drum	LGHB 2/180	TLSD series 250 ml refill	LGHB 2/SD250
Gas driven lubricators		Electro-mechanical lubricant dispensers	
LAGD series 60 ml	LAGD 60/HB2	TLMR 101 series 380 ml refill (incl. battery)	LGHB 2/MR380B
LAGD series 125 ml	LAGD 125/HB2	TLMR 201 series 380 ml refill	LGHB 2/MR380




Technical data			
Designation	LGHB 2/(pack size)		
DIN 51825 code	KP2N-20	Corrosion protection	
NLGI consistency class	2	Emcor: – standard ISO 11007	0-0
Thickener	Complex calcium sulphonate	– water washout test	0-0
Colour	Brown	– salt water test (100% seawater)	0-0 ¹⁾
Base oil type	Mineral	Water resistance	
Operating temperature range	-20 to +150 °C (-5 to +300 °F)	DIN 51 807/1, 3 hrs at 90 °C	1 max.
Dropping point DIN ISO 2176	>220 °C (>430 °F)	Oil separation	
Base oil viscosity		DIN 51 817, 7 days at 40 °C, static, %	1-3 at 60 °C (140 °F)
40 °C, mm ² /s	400-450	Lubrication ability	
100 °C, mm ² /s	26,5	R2F, running test B at 120 °C	Pass at 140 °C (285 °F)
Penetration DIN ISO 2137		Copper corrosion	
60 strokes, 10 ⁻¹ mm	265-295	DIN 51 811	2 max. at 150 °C (300 °F)
100 000 strokes, 10 ⁻¹ mm	-20 to +50 (325 max.)	Rolling bearing grease life	
Mechanical stability		ROF test	
Roll stability, 72 hrs at 100 °C, 10 ⁻¹ mm	-20 to +50 change	L ₅₀ life at 10 000 r/min., hrs	>1 000 at 130 °C (265 °F)
V2F test	'M'	EP performance	
		Wear scar DIN 51350/5, 1 400 N, mm	0,86 ¹⁾
		4-ball test, welding load DIN 51350/4, N	4 000 min.
		Fretting corrosion	
		ASTM D4170 (mg)	0 ¹⁾

¹⁾ Typical value

Lubrication management

Just as asset management takes maintenance to a higher level, a lubrication management approach allows lubrication to be seen from a wider point of view. This approach helps to effectively increase machine reliability at a lower overall cost.



skf.com | mapro.skf.com | skf.com/lubrication

© SKF is a registered trademark of the SKF Group.

© SKF Group 2017

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB MP/P8 12050/2 EN · June 2017

Certain image(s) used under license from Shutterstock.com.