

MOLYDUVAL Sekorex T 150

广州孚润 400-992-6811



Waterproof Tacky Chain Lubricant

High treated very tacky lubrication oil for many kinds of chains, especially for outside door chains. Contains a high percentage of synthetic tackifiers for better adhesion.

Properties

- * very good tackiness
- * resistant to water
- * high flash point
- * good ageing resistance
- * protects from wear
- * directly efficient
- * creeps into the gap of the chain
- * seal compatibility
- * very good water resistant
- * compatible and mixable with mineral oil

Applications

- * for industrial gears and thread spindles running slowly but loaded heavy
- * for chains, drive and transport chains, in conveying machines, pasteurize plants, sorting stations, peelers, packing and labelling machines, shrinking tunnels
- * for motorcycle chains

Technical Datas

Color		brown
Base Fluid		Min
Viscosity Class	ISO-VG	150
Temperature Range	°C	-20 -> 150
Pour point	°C	-20
Density 15°C	kg/m ³	890
Viscosity 40°C	mm ² /s	150
Flash Point	°C	ca.200
Viscosity Index		100

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence.