



Previous Name: Shell SRS 4000

Shell Gadus S3 A1300C 2

- Heavy Duty Protection
- Water resistant
- Red Calcium

Premium Heavy Duty Grease

Shell Gadus S3 A1300C is a calcium grease based on anhydrous calcium soaps and high viscous mineral oils, containing antioxidants, rust inhibitors, EP- and Anti-Wear additives. The grease has an excellent adhesion force, is very water repellent and has the ability to withstand severe shock loads.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- Excellent adhesion
- Water repellent
- Withstand severe shock loads

Main Applications



- Shell Gadus S3 A1300C is developed for the lubrication of heavily loaded journals and roller bearings operating in wet environment e.g. off-road equipments and vehicles, forestry and agricultural machines, marine and offshore.

- Fifth wheels
- Pins
- Bushings
- Joints
- Cranes
- Stern tube bearing/seals, shark jaws, trawl winches and general maintenance of machinery and equipment on-deck marine and offshore environment.

Specifications, Approvals & Recommendations

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Typical Physical Characteristics

Properties		Method	Shell Gadus S3 A1300C
NLGI Consistency			2
Penetration, worked 60 strokes (0.1 mm)	0.1mm	IP 50 / ASTM D217	265-295
Dropping Point	°C	IP 396	>140
Base Oil Viscosity	@40°C cSt	IP 71 / ASTM D445	1300
Base Oil Viscosity	@100°C cSt	IP 71 / ASTM D445	106
Rust Preventing Properties : SKF Emcor distilled water			Pass
Rust Preventing Properties : SKF Emcor WWO distilled water			Pass
Lubricating Ability SKF R2F A			Pass
Lubricating Ability SKF R2F B	@120°C		Pass
Water Washout		ASTM D1264	5%
Colour			Red
Temperature Range (temporarily)	°C		-25/+110(120)

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

- **Health and Safety**

Shell Gadus S3 A1300C is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

- **Advice**

Advice on applications not covered here may be obtained from your Shell representative.